

# 3 SERIES

## 10 - 66 kVA

**The attention to detail and high standards of engineering can be seen immediately in the AJ Power 3 Series.**

The smallest range from AJ Power, the 3 Series, offers reliable power in an ultra compact solution. The 3 Series is powered by the world renowned Perkins and Deutz engines and offers optimum fuel consumption. A range of options are available to tailor your generating set to meet your needs, including optional canopy offering low noise level - perfect for urban locations.

Also available within the 3 Series range is our telecomms generating set, offering an impressive solution for the telecommunications market. Integral high capacity fuel tanks and 500 hour service intervals are just a few of the many features of this model, specifically chosen to serve its purpose.



## Fuel Optimised

Model	50Hz				60Hz			
	Prime		Standby		Prime		Standby	
	kVA	kW	kVA	kW	kVA	kW	kVA	kW
<b>AJ10</b>	9.0	7.2	10.0	8.0	-	-	-	-
<b>AJ14</b>	13.0	10.4	14.3	11.4	-	-	-	-
<b>AJ17</b>	15.0	12.0	16.5	13.2	-	-	-	-
<b>AJ22</b>	20.0	16.0	22.0	17.6	-	-	-	-
<b>AJ33</b>	30.0	24.0	33.0	26.4	33.8	27.0	37.5	30.0
<b>AJ50</b>	45.0	36.0	50.0	40.0	56.3	45.0	62.5	50.0
<b>AJ66</b>	60.0	48.0	66.0	52.8	70.0	56.0	77.5	62.0

## Stage II Emissions Oil Cooled\*\*

Model	50Hz				60Hz			
	Prime		Standby		Prime		Standby	
	kVA	kW	kVA	kW	kVA	kW	kVA	kW
<b>AJ22</b>	20.0	16.0	22.0	17.6	23.8	19.0	26.3	21.0
<b>AJ33</b>	30.0	24.0	33.0	26.4	36.0	28.8	38.8	31.0
<b>AJ44</b>	42.0	33.6	44.0	35.2	48.7	39.0	50.6	40.5
<b>AJ64</b>	60.0	48.0	64.0	51.2	65.6	52.5	68.8	55.0

## Stage IIIA Emissions

Model	50Hz				60Hz			
	Prime		Standby		Prime		Standby	
	kVA	kW	kVA	kW	kVA	kW	kVA	kW
<b>AJ10</b>	9.0	7.2	10.0	8.0	11.3	9.0	12.5	10.0
<b>AJ14</b>	13.0	10.4	14.3	11.4	15.6	12.5	17.4	13.9
<b>AJ22</b>	20.0	16.0	22.0	17.6	22.5	18.0	25.0	20.0

Ratings based on 3ph, 400/230 Volt, 0.8pf, 50 Hz and 3 ph, 480/277 Volt, 0.8pf, 60 Hz

1 phase available - Refer to factory for further information

\*\*Stage II Emissions at 50Hz only.



**More details:** Full product specifications are available on request.